



Feature	BinPak	Vertical Compactor
• Lift height 24" (vs. 55 1/2") – fewer back strain injuries	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• High compaction ratio (approx. 6:1) – fewer pickups	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Sealed - prevents rodents, birds, wasps and other pests from entering	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Sealed – results in lower odour	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Steel lid prevents garbage springback when dumping – resulting in no waste blowing around & higher compaction ratio	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Truck alignment not important resulting in less equipment damage	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Easy & less costly installation (no bolt down required)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Easily relocated – no concrete lag bolts	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• More space around unit (smaller footprint)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Switches sealed to IP69K standards (1500 psi pressure wash)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• No waste blowing around – cleaner garbage area	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• Single phase 200-250VAC 30A power required with no changes to hardware	<input checked="" type="checkbox"/>	<input type="checkbox"/>
• May be situated inside a roofed enclosure, outside standalone, or fenced outside.	<input checked="" type="checkbox"/>	<input type="checkbox"/>